



Expedient Military Load Classification (MLC) Analysis for STANAG 2021 ed. 6.5 Meeting Review.



TECHNOLOGY DRIVEN. WARFIGHTER FOCUSED.

Brian K. Hornbeck

Deputy AD, Force Projection Technology

Office Phone: 586-574-5608

brian.hornbeck@us.army.mil

UNCLAS: DISTRIB A: Approved for public release

23 JUN 2009

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 23 JUN 2009		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Expedient Military Load Classification (MLC) Analysis for STANAG 2021 ed. 6.5 Meeting Review.				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Brian K. Hornbeck				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army RDECOM-TARDEC 6501 E 11 Mile Rd Warren, MI 48397-5000				8. PERFORMING ORGANIZATION REPORT NUMBER 19968	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S) TACOM/TARDEC	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) 19969	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES Presented at NATO STANAG meeting 29 JUN 2009, France, The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 14	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

- Five different MLC procedures were analyzed:
 - Scale readings with MLC software.
 - Scale readings using STANAG factor.
 - Current expedient method using Data Plate information
 - Tire contact area with tire pressure (Gross Tire Area)
 - Tire contact area with tire pressure (Tire Tread Area)
- Data was collected from 5 common US Army vehicles.
 - CBT empty
 - M984A2 Wrecker
 - LMTV
 - MRAP MaxxPro
 - MRAP MaxxPro plus.
- Data was summarized and compared with additional information collected from all 287 military vehicles.

- Data collected from scale in Fig.1 for each wheel.
- Applied in STANAG 2021 Reference software to determine the “True” MLC and create a control.

Table 1: Vehicle MLC’s calculated from software

Vehicle	Control MLC
CBT empty	17
Wrecker	24
LMTV	9
MRAP Maxx Pro	18
MRAP MaxxPro Plus	29



Figure 1: Scale Measurement

- Data collected from scale in Fig.1 for each wheel.
- Applied the current STANAG factor of 1.15.

Table 2: Vehicle MLC's calculated from scales

Vehicle	Control MLC	Scaled MLC
CBT empty	17	21
Wrecker	24	31
LMTV	9	11
MRAP Maxx Pro	18	21
MRAP MaxxPro Plus	29	28

- Data Plate Method
 - Gross vehicle weight from data plate (tons) x 1.15

Table 3: Comparison of Control and Data Plate Method MLC's

Vehicle	Control MLC	Data Plate MLC
CBT empty	17	38
Wrecker	24	55
LMTV	9	14
MRAP Maxx Pro	18	25
MRAP MaxxPro Plus	29	30

- Gross tire area Expedient Method:
 - Tire contact area was measured, shown in Fig 2.
 - Tire pressure was measured.
 - Wheel weights calculated:
contact area (in²) x tire pressure (psi).
 - Expedient method was applied:
Calculated Weight (tons) x 1.15



Figure2: Tire Area Measurement

Table 4: Comparison of Control and Gross Tire Area MLC's

Vehicle	Control MLC	Gross Area MLC
CBT empty	17	49
Wrecker	24	76
LMTV	9	21
MRAP Maxx Pro	18	31
MRAP MaxxPro Plus	29	50

- Tire Tread Area Expedient Method:
 - Tread pattern was copied onto graph paper to estimate area.
 - Wheel weights calculated:
 - Contact area (in²) x tire pressure (psi) x percent tire contact
 - Expedient method was applied: Calculated Weight (tons) x 1.15

Table 5: Comparison of Control and Tire Tread Area MLC's

Vehicle	Control MLC	Tire Tread Area MLC
CBT empty	17	23
Wrecker	24	36
LMTV	9	9
MRAP Maxx Pro	18	17
MRAP MaxxPro Plus	29	27

Table 6: F.S. for Calculated MLC's Using the STANAG 1.15 Factor

Vehicle	Control MLC	Scaled Method	Data Plate Method	Gross Tire Area	Tire Tread Area
CBT empty	1.0	1.22	2.23	2.89	1.36
Wrecker	1.0	1.27	2.28	3.18	1.50
LMTV	1.0	1.19	1.51	2.28	1.05
MRAP Maxx Pro	1.0	1.18	1.39	1.71	0.96
MRAP MaxxPro Plus	1.0	0.95	1.02	1.73	0.94
Ave F.S.	1.0	1.16	1.68	2.36	1.16

- Numbers Greater than 1 indicate an Over-estimation
- F.S. = Experimental MLC / Control MLC



Average Factor of Safety for 287 Wheeled Military Vehicles



Model #	Software Calc		Calculated Factor		Calculated Factor
	MLC	Weight (tonnes)	MLC/ mass (metric)	Weight (tons)	MLC/ mass (US)
M123 6x6 towing 6k water trailer	17	20.06	0.86	22.11	0.78
M123 6x6 towing 6k water trailer	38	43.81	0.87	48.29	0.79
M915 w/ XM 990 w XM21	17	20.07	0.86	22.12	0.78
M985	28	27.95	1.01	30.81	0.92
M978	25	25.32	0.98	27.91	0.89

Buffalo	30	25.40	1.17	28.00	1.07
Buffalo w/ Expedient Armor	38	30.84	1.24	34.00	1.12
Husky w/ Expedient Armor	10	9.98	0.96	11.00	0.87
JERRV w/ Expedient Armor	23	21.59	1.04	23.80	0.95
RG-31 MK5 w/ Expedient Armor	21	17.24	1.23	19.00	1.12

Average 1.04Average 0.94

Calculations of MLC using Factors and comparing F.S.

Metric MLC	F.S.
20	1.14
43	1.12
20	1.14
27	0.97
25	1.00

US Cust MLC	F.S.
20	1.14
43	1.13
20	1.14
27	0.97
25	1.00

25	0.83
30	0.79
10	1.03
21	0.94
17	0.79

Ave. F.S.: 1.00

25	0.84
30	0.79
10	1.03
21	0.94
17	0.79

Ave. F.S.: 1.00

	Factor	F.S
Original	1.25	1.27
Option	1.04	1.06
Proposed	1.08	1.1
	0.98	1


Factor	F.S
1.15	1.29
0.94	1.05
0.98	1.1
0.89	1

Factor Selection: 0.98

0.89


Data Comparison of 287 Wheeled Military Vehicles (US Tons)

% of Vehicle MLC's Overestimated vs. Calculated Factor (US Tons)



- Factor of 0.98 overestimates 80% of wheeled military vehicles with an average safety factor of 1.1
- Current factor of 1.15 overestimates 92% of wheeled military vehicles with an average safety factor of 1.29

% of Vehicle MLC's Overestimated vs. Calculated Factor (Metric Tons)



- Factor of 1.08 overestimates 80% of military vehicles with an average safety factor of 1.1
- Current factor of 1.25 overestimates 92% of military vehicles with an average safety factor of 1.27



MLCs for All Experimental Methods using 0.98



Table 7: MLCs Using the 0.98 Proposed Factor

Vehicle	Control MLC	Scaled Method MLC	Data Plate Method MLC	Gross Tire Area MLC	Tire Tread Area MLC
CBT empty	17	18	32	42	20
Wrecker	24	26	47	65	31
LMTV	9	9	12	17	8
MRAP Maxx Pro	18	18	21	26	15
MRAP MaxxPro Plus	29	24	25	43	23

Table 8: F.S. for Calculated MLC's Using the 0.98 Proposed Factor

Vehicle	Control MLC	Scaled Method	Data Plate Method	Gross Tire Area	Tire Tread Area
CBT empty	1.0	1.04	1.9	2.46	1.16
Wrecker	1.0	1.08	1.94	2.71	1.27
LMTV	1.0	1.02	1.28	1.94	0.89
MRAP Maxx Pro	1.0	1.0	1.18	1.46	0.82
MRAP MaxxPro Plus	1.0	0.81	0.87	1.48	0.8
Ave F.S.	1.0	0.99	1.44	2.01	0.99

- Numbers Greater than 1 indicate an Over-estimation
- F.S. = Experimental MLC / Control MLC

- Current STANAG Factors (1.25 and 1.15) overestimate the MLCs for 92% of the US Army's laden wheeled vehicles
- Current STANAG Factors result in an average F.S. of 1.27 and 1.29 respectively for US Army's wheeled vehicles
- These F.S. are in addition to the bridge's design F.S. which is 1.33 for mobile bridges and higher for civilian fixed bridges
- Proposed Factors of 1.08 and 0.98 overestimate 80% of the US Army's laden wheeled vehicles
- Both proposed metric and short ton Factors (1.08 and 0.98 respectively) results in an average F.S. of 1.1 for US Army's wheeled vehicles
- The experimental data showed the method of collection provides an additional F.S. thus supporting the reduction of the current STANAG Factors